

5位數微電腦型盤面式電錶(顯示幕0.8")

(5 DIGIT MICROPROCESS PANEL METER)(DISPLAY 0.8")

MODEL
MMX-1

CE



■特點(FEATURES)

- 精確度0.05%滿刻度±1位數(Accuracy 0.05% F.S.±1digit)
- 可量測交直流電流/交直流電壓/電位計/傳送器/Pt-100/熱電偶/荷重元/電阻等信號(Measuring DCA/DCV/ACA/ACV/Potentiometer/Transmitter/Pt-100/Termocouple/Load Cell/Resistor/etc.....)
- 顯示範圍-19999~99999可任意規劃(Programmable range-19999 to 99999 digit)
- 具有自動歸零或保持或開根號或雙顯示功能(Auto zero or hold or root or dual display function)(optional)
- 小數點可任意規劃(Decimal point can be modified)
- 尺寸小、穩定性高(Dimension small and High stability)

1.MODEL:MMX-1- □ □ □ □

(選購型號)

NO	Input Type	NO	DCV(ACV)	NO	DCA(ACA)	NO	Potentiometer	NO	Transmitter	NO	Pt-100	NO	Load Cell	NO	Thermocouple	NO	Aux.Power
A	DC	11	0~50mV	21	0~19.999uA	31	0~10%	41	DC4~20mA	51	-50.00~+50.00°C	61	2mV/V	71	J(-200~760°C)	A	AC110/220V
B	AC(RMS)	12	0~5V	22	0~199.99uA	32	0~50%	42	DC1~5V	52	-100.00~+100.00°C	62	3mV/V	72	K(-200~1360°C)	O	SPECIFIED
C	AC(TRMS)	13	0~10V	23	0~1.9999mA	33	0~100%	43	DC4~20mA	53	-200.0~+400.0°C	63	2mV/V	73	T(-200~395°C)		
D	Potentiometer	14	0~36V	24	0~19.999mA	34	5~95%	44	DC1~5V	54	-200.0~+850.0°C	64	3mV/V	74	E(-185~990°C)		•±20% of rate less 3VA for AC input (50/60Hz)
E	Transmitter	15	0~54V	25	0~199.99mA	35	10~90%	49	SPECIFIED	59	SPECIFIED	69	SPECIFIED	75	R(0~1760°C)		
F	Pt-100(RTD)	16	0~110V	26	0~2.000A	39	SPECIFIED	•Three wire connection •Exciting voltage DC20V (<25mA)	•41/42 nonexciting DC20V •43/44 exciting DC20V (<25mA)	•Three wire connection non-programmable	•61/62 Exciting DC5V(<100mA) •63/64 Exciting DC10V(<50mA)	76	S(0~1750°C)				
G	Thermocouple	17	0~600V	27	0~5.000A	77	B(200~1800°C)										
H	Load Cell	18	0~1000V	28	0~10.000A	•CJC traceability ±0.5°C (0~70°C)											
R	Resistor	19	SPECIFIED	29	SPECIFIED												

2.SPECIFICATION (主要規格)

- Measuring accuracy (精確度) (23±5°C) : 0.05% F.S.±1 digit
0.2% F.S.±1 digit(AC(RMS))
0.2% F.S.±0.5°C (CJC)
- Sampling time (取樣時間) : 16 cycles/sec.
- Readout range (顯示值範圍) : -19999~99999 digit adjustable
- Zero (offset) range (歸零調整範圍) : -19999~99999 digit adjustable
- Over input indication (過載顯示) : " doFL " or "-doFL"
- Display (顯示幕) : Red high efficiency LEDs high 20.32mm(0.8")
- Polarity display (極性顯示) : When input is negative " - " display
- Temp. coefficient (溫度係數) : 50ppm/°C (0~50°C)
- Parameter setting (參數設定方式) : Touch switches
- Memory mode (記憶型式) : Non-volatile E² PROM memory
- Dielectric strength (絕緣耐壓能力) : 2KVac/1 min. (input/power)
- Operating condition (使用環境條件) : 0~50°C (20 to 90% RH non-condensed)
- Storage condition (存放環境條件) : 0~70°C (20 to 90% RH non-condensed)
- CE EMC Certification (CE認證) : EN 55022:1998/A1:2000 Class A
EN 61000-3-2:2000
EN 61000-3-3:1995/A1:2001
EN 55024:1998/A1:2001

3.OUTSIDE DIMENSION AND CONNECTION DIAGRAM

(外型尺寸與開孔尺寸與配線圖)

